

Insulated crimped cable lugs



Insulated crimped cable lugs

SHARE 

- For fine and superfine stranded conductors, e.g. to DIN EN 60228 Cl. 5 and 6
- According to DIN 46237
- High-quality brazing process in the crimping area
- Insulation sleeve, halogen-free



Features

- Temperature resistance: up to 105 °C
- Easy-Entry insulation for simple cable insertion
- Cross-section-dependent colour-coding

Material

- Copper (ETP)
- Insulation sleeve: PA

Surface

- Tin-plated to protect against corrosion

Additional information


- * = not standardised
- 0.1 - 0.4 mm² not CSA-tested

Compatibility

CABLE TYPE

Display

CABLE TYPE	DESCRIPTION
------------	-------------



Fine-strand conductor (Class 5 according to DIN EN 60228) made from bright finish or metal-encased annealed copper



Extra-fine-strand conductor (Class 6 according to DIN EN 60228) made from bright finish or metal-encased annealed copper

Ordering Information

ORDERING INFORMATION

Display

PART NO.	NOMINAL CROSS-SECTION MM ²	NOMINAL SIZE ACCORDING TO DIN	COLOUR	NOTE	DIMENSIONS MM								WEIGHT/100 PCS. ~KG
					D1	D2	D4	L	S	D3	A1	A2	

PART NO.	NOMINAL CROSS-SECTION MM ²	NOMINAL SIZE ACCORDING TO DIN	COLOUR	NOTE	DIMENSIONS MM								WEIGHT/100 PCS. ~KG	
					D1	D2	D4	L	S	D3	A1	A2		
6192	0,1-0,4	--		*	1,0	2,3	2,2	14,0	0,5	5,0	-	--	0,020	-
61925	0,1-0,4	--		*	1,0	2,6	2,2	14,0	0,5	5,0	-	--	0,020	-
6193	0,1-0,4	--		*	1,0	3,3	2,2	14,0	0,5	5,0	-	--	0,020	-
61935	0,1-0,4	--		*	1,0	3,8	2,2	16,0	0,5	6,5	-	--	0,025	-
6194	0,1-0,4	--		*	1,0	4,4	2,2	16,0	0,5	7,0	-	--	0,025	-
6195	0,1-0,4	--		*	1,0	5,4	2,2	15,0	0,5	8,0	-	--	0,025	-
62025	0,5-1	2,5-1		-	1,6	2,8	4,5	16,5	0,8	6,0	5	10,5	0,060	
6203	0,5-1	3,0-1		-	1,6	3,2	4,5	16,5	0,8	6,0	5	10,5	0,060	
62035	0,5-1	3,5-1		-	1,6	3,7	4,5	16,5	0,8	6,0	5	10,5	0,550	
6204	0,5-1	4,0-1		-	1,6	4,3	4,5	17,5	0,8	8,0	5	10,5	0,070	
6205	0,5-1	5,0-1		-	1,6	5,3	4,5	18,5	0,8	10,0	5	10,5	0,090	
6206	0,5-1	--		*	1,6	6,5	4,5	20,5	0,8	11,0	5	10,5	0,080	

PART NO.	NOMINAL CROSS-SECTION MM ²	NOMINAL SIZE ACCORDING TO DIN	COLOUR	NOTE	DIMENSIONS MM								WEIGHT/100 PCS. ~KG
					D1	D2	D4	L	S	D3	A1	A2	
6208	0,5-1	--		*	1,6	8,4	4,5	22,5	0,8	14,0	5	10,5	0,130
62010	0,5-1	--		*	1,6	10,5	4,5	24,5	0,8	18,0	5	10,5	0,130
6303	1,5-2,5	3,0-2,5		-	2,3	3,2	5,1	17,5	0,8	6,0	5	11,5	0,065
63035	1,5-2,5	3,5-2,5		-	2,3	3,7	5	17,5	0,8	6,0	5	11	0,065
6304	1,5-2,5	4,0-2,5		-	2,3	4,3	5,1	18,5	0,8	8,0	5	11,5	0,080
6305	1,5-2,5	5,0-2,5		-	2,3	5,3	5,1	20,5	0,8	10,0	5	11,5	0,090
6306	1,5-2,5	6,0-2,5		-	2,3	6,5	5,1	22,5	0,8	11,0	5	11,5	0,110
6308	1,5-2,5	8,0-2,5		-	2,3	8,4	5,1	23,5	0,8	14,0	5	11,5	0,130
63010	1,5-2,5	--		*	2,3	10,5	5,1	25,5	0,8	18,0	5	11,5	0,160
6504	4-6	4,0-6		-	3,6	4,3	6,5	20,5	1,0	8,0	6	12,5	0,140
6505	4-6	5,0-6		-	3,6	5,3	6,5	21,5	1,0	10,0	6	12,5	0,160
6506	4-6	6,0-6		-	3,6	6,5	6,5	22,5	1,0	11,0	6	12,5	0,170
6508	4-6	8,0-6		-	3,6	8,4	6,5	25,5	1,0	14,0	6	12,5	0,220

PART NO.	NOMINAL CROSS-SECTION MM ²	NOMINAL SIZE ACCORDING TO DIN	COLOUR	NOTE	DIMENSIONS MM								WEIGHT/100 PCS. ~KG
					D1	D2	D4	L	S	D3	A1	A2	
65010	4-6	10,0-6		-	3,6	10,5	6,5	27,5	1,0	18,0	6	12,5	0,290
65012	4-6	--		*	3,6	13,0	6,5	27,5	1,0	18,0	6	12,5	0,320

