

Always. Reliable. Tight.

Standard press seal

with infinitely super segmented ring technology

HSD150 SSG 1x70-112 b40 A2/EPDM55

Article no.: 3030300064, GTIN: 4052487223751



- **optical and tangible installation security due to integrated control opening**
- **Integrated super segmented ring technology for individual adjustment to cable diameter on site**
- **Segments with exact diameter marking**



Picture may differ from selected product

For sealing new pipes to be installed or pipes that have already been laid in core drills or wall sleeves. Infinitely adjustable to cable diameters on site.

FACTS

Application range:

- DIN 18533 W1.1-E, DIN 18533 W1.2-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

Advantages:

- Split as standard for retrofit installation
- Different material combinations are available for tailor-made applications
- Available from stock

Dimensions:

- Sealing width up to Ø 250 mm: 40 mm
- Sealing width for Ø 300 mm: 50 mm

Properties:

- U-profile: maximum stability for press segments

Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Rubber: EDPM or NBR

Tightness:

- Gastight and watertight

FEATURES

Wall sleeve/core drilled hole ID (mm):	150
Suitable for medium pipe OD (mm):	70 – 112
Packing unit (pieces):	15

PICTURES

