

Always. Reliable. Tight.

Polymer flange for retrofit dowelling

HSI150 DFK

Article no.: 2118010020, GTIN: 4052487156264



- **With integrated spirit level**

For retrofit dowelling using core drills or for screwing onto housing.
Facilitates gastight and watertight connection of system seals for
cables and cable ducts.



Picture may differ from selected product

FACTS

Application range:

- DIN 18533 W1.1-E, DIN 18533 W1.2-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, Waterproof concrete stress class 2

Advantages:

- System seal can be connected (e.g. cable duct connection or cable seal)
- Can be installed on container walls
- Form-closed surface seal

Scope of delivery:

- Fastening elements inclusive sealing rings
- Surface seal, 6 mm thick

Dimensions:

- Length x width: 235 x 235 mm
- Recommended centre distance for core drills: 250 mm
- Core drills max. Ø: 150 mm
- Structure in front of wall including surface seal: 63 mm

Material:

- Flange: glass fibre reinforced polyamide
- Surface seal: EPDM
- Fastening elements: V4A (AISI 316L)

Tightness:

- Gastight and watertight to 2.5 bar

PICTURES



ACCESSORIES REQUIRED



EGO sealant