



Actual

Catalog Number: LFH-SP20/50M
Product ID: 7TCA296130R0009
EAN Number: 05020963000751
Status: Active

Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, IP54 and IP65 Rating, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 50 Meters, Black

- High UV resistance
- Medium flexibility
- Medium fatigue life
- High mechanical strength
- Enhanced low fire hazard
- Halogen free
- Self extinguishing
- Food Industry
- Public Buildings

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	Adaptaflex
Type	Medium Flexibility Conduit
Special Features	High UV Protection, Low Fire Hazard
Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Trade Size	1/2 Inch
Outside Diameter	21.5mm
Inside Diameter	16.9mm
Length	50 m
Radius	45mm
Flexibility	Medium
Material	Galvanized Steel Core with LFH Jacket
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	20mm
Outer diameter	21.5mm
Inner diameter	16.9mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	Other
Operating temperature	-25-+90°C
Degree of protection (IP)	IP65
Weight	0.312kg/m
Colour	Black
Bending strength	Flexible

Packaging

Outer Quantity	1
Outer Dimensions (inches)	16x17x16
Weight Uom	35.5 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com