



Actual

Catalog Number: LFH-SP25/50M
Product ID: 7TCA296130R0013
UPC Number: 78621024857
EAN Number: 05020963046667
Status: A

Low Fire Hazard, Medium Flexibility Conduit, 3/4 Inch, Nominal Conduit Size 25mm, Outside Diameter 26.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, IP54 and IP65 Rating, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 50 Meters, Black

- High UV resistance
- Medium flexibility
- Medium fatigue life
- High mechanical strength
- Enhanced low fire hazard
- Halogen free
- Self extinguishing
- Food Industry
- Public Buildings

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Type	Medium Flexibility Conduit
Special Features	High UV Protection, Low Fire Hazard
Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Trade Size	3/4 in
Outside Diameter	26.0 mm
Inside Diameter	21.4 mm
Length	50 m
Radius	55 mm
Flexibility	Medium
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	25mm
Outer diameter	26mm
Inner diameter	21.4mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	Other
Operating temperature	-25-+90°C
Degree of protection (IP)	IP65
Weight	0.37kg/m
Colour	Black
Bending strength	Flexible

Packaging

Outer Quantity	7
Outer Dimensions (inches)	17x37x17
Weight Uom	40.81 lbs. Each



For further technical assistance, please contact us...

ABB Installation Products - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com