



Catalog Number: Product ID:

UPC Number:

EAN Number:

LTC125-TB

7TAD012610R0012

78621078957

05414363155157

Status: A

Industrial Grade, Type B Liquidtight Flexible PVC Conduit, 1-1/4 Inch Conduit Size, Approved for Outdoor and Direct Burial in the US, UL Temperature Ratings - 105 Degrees C Dry, 60 Degree C Wet, 70 Degree C Oil, CSA Temperature Rating 18 to 75 Degrees C, Oil Resistant, Voltage Rating 600V, Black with Orange Markings

- · Fast installation, even in tight or cramped spaces.
- · Smooth inner diameter allows easy wire pulling.
- Smooth outer jacket uses material approved for outdoor use, is sunlight resistant and oil resistant.
- · Lightweight and liquidtight.



Actual

Actual

North American Specifications	(UNSPSC)
UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Туре	Liquidtight Flexible Non-Metallic Conduit
Special Features	The Smooth Inner Surface Ensures that Cables and
	Conductors Can Be Fed Through Very Easily
Application	Machine Tools, Motor Hookups, Food Processing
	Equipment, Extensions from Wire Ways, and Sen-
	sor and Micro Switch Wiring Found In Control Con-
	soles.
Standard	UL E95745, CSA
Trade Size	1-1/4 in
Outside Diameter	42.2 mm
Inside Diameter	35.1 mm
Length	30.5 m
Voltage Rating	600 V
Material	PVC
Color	Black

European Specifications (ETIM)	
ETIM	EC001177 Protective plastic hose
Nominal size in inch	1 1/4 inch
Material	PVC
Operating temperature	-18-+105°C
Flexibility	Flexible
Colour	Black
Approved according to CSA	Υ

Packaging	
Outer Quantity	100
Outer Dimensions (inches)	27x26.5x9.5
Weight Uom	37.13 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet TDS000138

For further technical assistance, please contact us...

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 ABB Installation Products Technical Support MS 3B-50

860 Ridge Lake Blvd.

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289



www.tnb.com Memphis, TN 38120 Fax: (901) 252-132

Fax: (901) 252-1321 Email:techsupport@tnb.com