

 Catalog Number:
 LTXES06B-B

 Product ID:
 7TAA012LE0R0005

 UPC Number:
 78621010677

 EAN Number:
 05415022390780

Status: A



Liquid Tight Flexible Metallic Conduit, Extreme Temperature Range, Galvanised Steel Core with TPR Jacket, Conduit Size 1-1/2 Inch, Length 15 Meters/50 Feet, Working Temperature -60 to 150 Degrees C, Intermitting to 165 Degrees C, Compliant to RoHS, Black

Extreme temperature, CE compliant Liquid-tight FlexibleMetallic Conduits provide excellent performance inextreme low and high temperature environments

- Coordinated performance with Series 52/53 Steel Fittings
- Ingress protection ratings aligned with industrial enclosures
- Smooth extruded jackets provide best performance with fittings
- Ideal for machine and equipment, OEMs, panel builders and industrial, light manufacturing, commercial and outdoor installations
- · Liquid tight applications against water, oils and mild acids
- For use in electrical circuits up to 1,000 volts

North American Specifications (UNSPSC)	
UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Туре	Liquid Tight Flexible Metallic Conduit
Special Features	Designed to meet UL 360 ID/OD dimension require-
	ments
Application	Used in extremely high temperature applications
	such as commercial ovens and refrigeration, indus-
	trial furnaces and foundries
Standard	RoHS
Trade Size	1-1/2 in
Outside Diameter	1.900 in
Inside Diameter	1.575 in
Length	50 ft ; 15 m
Radius	114 mm
Material	Galvanised Steel
Finish	TPR Jacket

European Specifications (ETIM)	
ETIM	EC001179 Protective metallic hose
Nominal diameter	50mm
Nominal size in inch	1 1/2 inch
Outer diameter	48.26mm
Inner diameter	40.01mm
Material	Steel
Surface protection	Untreated
Sheathing material 1st coating	Megolon, flame retardant
Operating temperature	-60-+150°C
Degree of protection (IP)	IP67
Weight	1.55kg/m
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23	Υ
With approval according to UL	N
Approved according to CSA	N

Representative



Packaging	
Outer Quantity	50
Outer Dimensions (inches)	33.62x37x10.38
Weight Uom	1.04 lbs. Each
Documents / Support Tools	
Technical Drawing / Data Sheet	TDS000006
Technical Drawing / Data Sheet	TDS000117
Support/Tools	Available on Website

Available on Website

For further technical assistance, please contact us...

ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120

Catalog US

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com