



Actual

**Catalog Number:** S75/10M  
**Product ID:** 7TCA296010R0187  
**EAN Number:** 05020963061196  
**Status:** Active

Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 75mm, Outside Diameter 77.0mm, Inside Diameter 70.0mm, Static Bend Radius 150mm, Reel Length 10 Meters, Galvanised Steel General Purpose

- Very high UV resistance
- High flexibility
- High fatigue life
- High mechanical strength
- Inherent low fire hazard and halogen free
- Lighting/Cable Track
- Under floor Wiring
- Light Industrial

#### North American Specifications (UNSPSC)

|                  |                                                  |
|------------------|--------------------------------------------------|
| UNSPSC           | 39131706 Electrical conduit                      |
| IGCC             | 5535 Electrical conduit                          |
| Brand Name       | Adaptaflex                                       |
| Type             | Low Fire Hazard Conduit                          |
| Special Features | Very High UV Protection and Fatigue Life         |
| Application      | Indoors / Outdoors - Light Industrial, Buildings |
| Trade Size       | 2-1/2 Inches                                     |
| Outside Diameter | 77.0mm                                           |
| Inside Diameter  | 70.0mm                                           |
| Length           | 10 m                                             |
| Radius           | 150mm                                            |
| Flexibility      | Very High                                        |
| Material         | Galvanized Steel                                 |

#### European Specifications (ETIM)

|                                |                                   |
|--------------------------------|-----------------------------------|
| ETIM                           | EC001179 Protective metallic hose |
| Nominal diameter               | 75mm                              |
| Outer diameter                 | 77mm                              |
| Inner diameter                 | 70mm                              |
| Material                       | Steel                             |
| Surface protection             | Other                             |
| Sheathing material 1st coating | Not sheathed                      |
| Operating temperature          | -50-+300°C                        |
| Degree of protection (IP)      | IP40                              |
| Weight                         | 1.525kg/m                         |
| Colour                         | Metallic                          |
| Bending strength               | Flexible                          |

#### Packaging

|                           |                 |
|---------------------------|-----------------|
| Outer Quantity            | 1               |
| Outer Dimensions (inches) | 1x1x1           |
| Weight Uom                | 33.62 lbs. Each |

#### Header

|          |                      |
|----------|----------------------|
| 3D Model | Available on Website |
|----------|----------------------|

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)