



Actual

Catalog Number: SP12/BL/25M
Product ID: 7TCA296020R0049
EAN Number: 05020963001123
Status: Active

Liquid Resistant, General Purpose, Highly Flexible Conduit, Nominal Conduit Size 12mm, Outside Diameter 14.0mm, Inside Diameter 10.3mm, Static Bend Radius 30mm, Reel Length 25 Meters, PVC Jacket with Galvanised Steel Core, Black

- Very high UV resistance
- High flexibility
- Medium fatigue life
- High mechanical strength
- Self extinguishing

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	Adaptaflex
Type	High Flexibility Conduit
Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Trade Size	5/16 Inch
Outside Diameter	14.0mm
Inside Diameter	10.3mm
Length	25 Meters
Radius	30mm
Flexibility	High
Material	Galvanized Steel Core with PVC Jacket
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	12mm
Outer diameter	14mm
Inner diameter	10.3mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	PVC
Operating temperature	-25-+70°C
Degree of protection (IP)	IP65
Weight	0.148kg/m
Colour	Black
Bending strength	Flexible

Packaging

Outer Quantity	1
Outer Dimensions (inches)	17x37x17
Weight Uom	8.29 lbs. Each

Header

3D Model Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.

T&B Technical Support
MS 3B-50

Hours: 7AM - 6PM CDT
Monday-Friday

Memphis, TN 38120
www.tnb.com

860 Ridge Lake Blvd.
Memphis, TN 38120

Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com