



Actual

Catalog Number: **SPLHC20/25M**
Product ID: 7TCA296030R0340
UPC Number: 78621024564
EAN Number: 05020963005824
Status: A

Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 20mm, 1/2 Inch US Conduit Size, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanized Steel Core, Black

- Very high UV resistance
- Very High flexibility
- High fatigue life
- High mechanical strength
- Self extinguishing and halogen free
- Machine Building
- Extreme Temperature Environments

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Type	Extreme Temperature Flexible Conduit
Application	Liquid Tight - Extreme Temperature Environments
Trade Size	1/2 in ; NC20
Outside Diameter	21.1 mm
Inside Diameter	15.9 mm
Length	25 m
Radius	80 mm
Flexibility	Medium
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	20mm
Outer diameter	21.1mm
Inner diameter	15.9mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	Other
Operating temperature	-65-+135°C
Degree of protection (IP)	IP68
Weight	0.4kg/m
Colour	Black
Bending strength	Flexible

Packaging

Outer Quantity	6
Outer Dimensions (inches)	17x37x17
Weight Uom	22.47 lbs. Each

Header

3D Model	Available on Website
----------	----------------------



For further technical assistance, please contact us...

ABB Installation Products - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com