



Actual

Catalog Number: **SPLHC25/10M**
Product ID: 7TCA296030R0343
EAN Number: 05020963072413
Status: Active

Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 10 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Adaptaflex
Type	Extreme Temperature Flexible Conduit
Application	Liquid Tight - Extreme Temperature Environments
Trade Size	3/4 Inch/NC 25mm
Outside Diameter	26.4mm
Inside Diameter	21.0mm
Length	10 Meters
Radius	110mm
Flexibility	Medium
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	25mm
Outer diameter	26.4mm
Inner diameter	21mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	Other
Operating temperature	-65-+135°C
Degree of protection (IP)	IP68
Weight	0.48kg/m
Colour	Black
Bending strength	Flexible

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	10.74 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com