



Actual

Catalog Number: SSB32/10M
Product ID: 7TCA296100R0194
UPC Number: 78621026073
EAN Number: 05020963047657
Status: A

Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 32mm, Outside Diameter 34.0mm, Inside Diameter 28.1mm, Static Bend Radius 60mm, Reel Length 10 Meters, 316 Stainless Steel Core and Overbraid

- Very high UV resistance
- High flexibility
- High fatigue life
- High mechanical strength, high abrasion resistance
- Inherent low fire hazard and halogen free
- Standard EMI screen rating
- Marine
- Corrosive Environments

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Type	Low Fire Hazard Conduit
Special Features	Very High UV Protection and High Fatigue Life
Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Trade Size	1 in
Outside Diameter	34.0 mm
Inside Diameter	28.1 mm
Length	10 m
Radius	60 mm
Flexibility	High
Material	Stainless Steel Core and Overbraid

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	32mm
Outer diameter	34mm
Inner diameter	28.1mm
Material	Stainless steel
Surface protection	Untreated
Sheathing material 1st coating	Stainless steel wire
Operating temperature	-50-+300°C
Degree of protection (IP)	IP40
Weight	0.36kg/m
Colour	Metallic
Bending strength	Flexible

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	7.94 lbs. Each

Header

3D Model	Available on Website
----------	----------------------



For further technical assistance, please contact us...

ABB Installation Products - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com