



Enlargement cable gland



Reducing rings



Screw plug



Blanking plug

Ordering details

| Thread | Cable Ø mm seal. 1+2 | seal. 2 | A/F mm | L mm | E mm | Weight kg | OU | Order No. (-20 °C up to +70 °C) | Order No. (-40/-55 °C up to +70 °C) |
|--------|-------------------------|---------|-----------|---------|---------|--------------|----|------------------------------------|--|
|--------|-------------------------|---------|-----------|---------|---------|--------------|----|------------------------------------|--|

Multiple cable glands -black

| | | | | | | | | | |
|-----------|-------------|--|----|------|----|-------|----|--------------------|-----|
| M25 x 1.5 | 2 x 4.5 - 7 | | 29 | 29.5 | 8 | 0.019 | 20 | GHG 960 1955 R0054 | --- |
| M32 x 1.5 | 4 x 4.5 - 7 | | 36 | 35.5 | 10 | 0.030 | 20 | GHG 960 1955 R0055 | --- |

Slotted cable glands for special cables:

(Breakout-internal cable type orange/ Ultra-Fox Plus type 903 AG 621 02 709/ Ehret / ICS 24 type 84 305 ... 2)

| | | | | | | | | | |
|-------------------------------|--|--|----|------|---|-------|----|--------------------|--|
| M20 x 1.5 black ²⁾ | | | 24 | 25.0 | 8 | 0.010 | 20 | GHG 960 1955 R0403 | |
| M20 x 1.5 blue ²⁾ | | | 24 | 25.0 | 8 | 0.010 | 20 | GHG 960 1955 R0413 | |

Enlargement cable glands (reduced thread diameter)

| | | | | | | | | | |
|---------|---------|-------------------------|----|------|----|-------|----|--------------------|--|
| M16/M20 | 7 - 9 | 9.5 - 13 | 24 | 25.0 | 12 | 0.010 | 20 | GHG 960 1956 R0002 | |
| M20/M25 | 10 - 13 | 13.5 - 17.5 | 29 | 29.5 | 13 | 0.018 | 20 | GHG 960 1956 R0003 | |
| M25/M32 | 14 - 17 | 17.5 - 21 | 36 | 35.5 | 13 | 0.029 | 20 | GHG 960 1956 R0004 | |
| M32/M40 | 19 - 22 | 22.0 - 28 | 46 | 39.5 | 15 | 0.046 | 10 | GHG 960 1956 R0005 | |
| M40/M50 | 24 - 28 | 28.0 - 35 | 55 | 44.0 | 15 | 0.073 | 10 | GHG 960 1956 R0006 | |
| M50/M63 | 29 - 35 | 36.0 - 48 ¹⁾ | 68 | 47.0 | 16 | 0.116 | 5 | GHG 960 1956 R0007 | |

| | E mm | Ø D mm | Weight kg | OU | Order No. (-55 °C up to +70 °C) |
|--|---------|-----------|--------------|----|------------------------------------|
|--|---------|-----------|--------------|----|------------------------------------|

Blanking plug for cable glands

| | | | | | |
|-----|------|------|-------|----|--------------------|
| M12 | 30.3 | 6.0 | 0.001 | 20 | GHG 960 1944 R0101 |
| M16 | 33.0 | 7.0 | 0.001 | 20 | GHG 960 1944 R0102 |
| M20 | 34.5 | 8.5 | 0.002 | 20 | GHG 960 1944 R0103 |
| M25 | 36.0 | 11.0 | 0.003 | 20 | GHG 960 1944 R0104 |
| M32 | 39.5 | 14.0 | 0.005 | 20 | GHG 960 1944 R0105 |
| M40 | 42.0 | 20.0 | 0.018 | 10 | GHG 960 1944 R0106 |
| M50 | 44.0 | 26.0 | 0.033 | 10 | GHG 960 1944 R0107 |
| M63 | 45.0 | 34.0 | 0.108 | 5 | GHG 960 1944 R0108 |

| Thread | L mm | E mm | Ø D mm | Weight kg | OU | Order No. (-55 °C up to +70 °C) |
|--------|---------|---------|-----------|--------------|----|------------------------------------|
|--------|---------|---------|-----------|--------------|----|------------------------------------|

Screw plug

| | | | | | | |
|-----------|-----|----|------|-------|----|--------------------|
| M16 x 1.5 | 4.0 | 12 | 21.5 | 0.002 | 20 | GHG 960 1952 R0111 |
| M20 x 1.5 | 4.0 | 13 | 25.5 | 0.004 | 20 | GHG 960 1952 R0112 |
| M25 x 1.5 | 4.0 | 13 | 30.5 | 0.007 | 20 | GHG 960 1952 R0113 |
| M32 x 1.5 | 5.5 | 15 | 37.5 | 0.013 | 10 | GHG 960 1952 R0114 |
| M40 x 1.5 | 5.5 | 15 | 45.5 | 0.020 | 10 | GHG 960 1952 R0115 |
| M50 x 1.5 | 5.5 | 16 | 55.5 | 0.030 | 5 | GHG 960 1952 R0116 |
| M63 x 1.5 | 6.5 | 16 | 85.0 | 0.040 | 5 | GHG 960 1952 R0117 |

¹⁾ M63 with additional sealing

²⁾ Cable dimensions and ambient temperatures see operating instruction

Cable glands with PG-thread are available on request.

The order No. will show 1 pcs. Please note that only order units (OU) can be ordered.