

PRODUCT-DETAILS

SPLHC25/25M

XTR.TEMP UR LIQ.TIGHT NC25 25MT BLK



General Information

Extended Product Type	SPLHC25/25M
Product ID	7TCA296030R0345
EAN	5020963005985
Catalog Description	XTR.TEMP UR LIQ.TIGHT NC25 25MT BLK
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 25mm, 3/4 Inch US Conduit Size, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Product Type	Extreme Temperature Flexible Conduit

Ordering

EAN	5020963005985
UPC	786210245676
Customs Tariff Number	8307106000

Dimensions

Product Net Depth / Length	25 m
----------------------------	------

Technical

Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Thermoplastic Rubber Cover

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	10 in 254 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHC25/25M
Instructions and Manuals	SPLHC25/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications

ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

