

BAND-IT[®]

PRODUCT



ULTRA-LOK[®] SYSTEM

Designed for quick installation, highest clamping force and gap-free inside diameter. The best choice for harsh duty applications!

Apply 3-5 times faster than band and buckle hand tools

Unique lock formed under full tension maximizing tightness

Available as free-end band and buckle or preformed clamps

201 1/4 hard SS band provides greater material strength allowing tighter clamps and can be double wrapped for additional strength

Alloy 625 Ultra-Lok Band is available*

Buckle hood protects lock from snags

Installs quickly with the UL4000-D
cordless tool

ULTRA-LOK[®] SYSTEM PRODUCT SPECIFICATIONS

PART NO.	MATERIAL	WIDTH (MM)	LENGTH (MM)	THICKNESS (MM)	MAX. DIA. SINGLE WRAP (MM)	MAX. DIA. DOUBLE WRAP (MM)	PACKAGE QUANTITY	WEIGHT (KG)
Ultra-Lok Band								
UL1018**	201 SS	12.7	457	0.76	76	not suggested	50/Box	1.9
UL1024**	201 SS	12.7	610	0.76	127	64	50/Box	2.4
UL1032**	201 SS	12.7	813	0.76	178	89	50/Box	3.3
UL1046**	201 SS	12.7	1168	0.76	280	140	25/Box	2.7
UL1070**	201 SS	12.7	1778	0.76	457	229	25/Box	3.9
UL1096**	201 SS	12.7	2438	0.76	635	318	25/Box	5.1
UL1116**	201 SS	12.7	2946	0.76	787	394	25/Box	6.0
UL2030	201 SS	19.05	762	0.76	203.2	96.5	25/Box	2.39
UL2042	201 SS	19.05	1067	0.76	299.7	144.8	25/Box	3.18
UL2060	201 SS	19.05	1524	0.76	444.5	218.4	25/Box	4.66
UL2084	201 SS	19.05	2134	0.76	640.1	315	25/Box	6.70
UL2120	201 SS	19.05	3048	0.76	929.6	462.3	25/Box	9.32
Ultra-Lok Buckles								
UB2549	201 SS	12.7					100/Box	1.1
UB2569	201 SS	19.1					100/Box	1.7

** 1/2" Bands will require M09387 for UL4000 Tool.

Preformed Ultra-Lok Clamps

PART NO.	MATERIAL	WIDTH (MM)	THICKNESS (MM)	INSIDE DIAMETER (MM)	WEIGHT (KG)	PACKAGE QUANTITY
UL2279	201 SS	19.1	0.76	50	6.8	100/Box

PART NO.	MATERIAL	WIDTH (MM)	THICKNESS (MM)	INSIDE DIAMETER (MM)	WEIGHT (KG)	PACKAGE QUANTITY
UL2109	201 SS	19.1	0.76	69	4.2	50/Box
UL2119	201 SS	19.1	0.76	76	4.7	50/Box
UL2129	201 SS	19.1	0.76	88	4.9	50/Box
UL2139	201 SS	19.1	0.76	101	2.9	25/Box
UL2149	201 SS	19.1	0.76	114	3.2	25/Box
UL2159	201 SS	19.1	0.76	127	3.4	25/Box
UL2709	201 SS	19.1	0.76	133	3.3	25/Box
UL2169	201 SS	19.1	0.76	152	3.8	25/Box
UL2179	201 SS	19.1	0.76	165	4.6	25/Box
UL2189	201 SS	19.1	0.76	177	4.4	25/Box
UL2199	201 SS	19.1	0.76	203	5	25/Box
UL2289	201 SS	19.1	0.76	228	2.31	10/Box

Alloy 625 Ultra-Lok Band

PART NUMBER	MATERIAL	WIDTH (MM)	LENGTH (MM)	MAXIMUM CLAMP DIAMETER	
				SINGLE WRAP (MM)	DOUBLE WRAP (MM)
Contact Us for Part Number & Minimum Order Quantity	Alloy 625	19.1	508	102	not suggested
	Alloy 625	19.1	610	127	not suggested
	Alloy 625	19.1	711	152	not suggested
	Alloy 625	19.1	813	178	89
	Alloy 625	19.1	914	252	102
	Alloy 625	19.1	1016	254	127
	Alloy 625	19.1	1118	267	140
	Alloy 625	19.1	1219	305	153
	Alloy 625	19.1	1321	330	165
	Alloy 625	19.1	1524	381	191
	Alloy 625	19.1	1727	445	216
	Alloy 625	19.1	1930	508	254
	Alloy 625	19.1	2134	559	280
	Alloy 625	19.1	2337	622	305
	Alloy 625	19.1	3048	826	407
	Alloy 625	19.1	3810	1029	508
	Alloy 625	19.1	4445	1232	610

*Regional specifications vary, some items may be subject to minimum order quantities or extended lead times, 3/4" band is available in plastic totes in the US