



Copper tube terminal

SC





● SC series terminal is made from T2 copper tube, via the tinning treatment, can avoid oxidation, the size of special copper tube makes the electrical conductivity is the best, and guarantees mechanical strength. After high temperature annealing treatment, the ductility is optimal.

*If you have special needs, please contact Tianze Electric Power Group

Conductor size mm ²	Stud mm	Part No.	Dimension mm				MOQ/Bag
			B	L	φd	L1	
1.5	4	SC1.5-4	8.0	16	1.8	5	500
	5	SC1.5-5	10.0	17	1.8	5	500
	6	SC1.5-6	10.0	18	1.8	5	500
2.5	4	SC2.5-4	8.0	18	2.4	7	500
	5	SC2.5-5	10.0	20	2.4	7	500
	6	SC2.5-6	10.0	20	2.4	7	500
4	8	SC2.5-8	12.5	23	2.4	7	500
	4	SC4-4	10.0	20	3.1	7	500
	5	SC4-5	10.0	20	3.1	7	500
6	6	SC4-6	12.0	20	3.1	7	500
	8	SC4-8	12.5	23	3.1	7	500
	4	SC6-4	10.0	24	3.8	9	500
10	5	SC6-5	10.0	24	3.8	9	500
	6	SC6-6	12.0	24	3.8	9	500
	8	SC6-8	15.0	26	3.8	9	500
16	10	SC6-10	15.0	28	4.0	9	500
	5	SC10-5	12.0	25	4.5	9	500
	6	SC10-6	12.0	25	4.5	9	500
25	8	SC10-8	12.5	27	4.5	9	500
	10	SC10-10	15.0	29	4.5	9	500
	12	SC10-12	17.0	31	4.5	9	500
35	5	SC16-5	12.0	30	5.4	12	500
	6	SC16-6	12.0	30	5.4	12	500
	8	SC16-8	12.5	30	5.4	12	500
50	10	SC16-10	16.0	33	5.4	12	500
	12	SC16-12	17.0	35	5.4	12	500
	5	SC25-5	13.0	33	6.8	12	300
70	6	SC25-6	13.0	33	6.8	12	300
	8	SC25-8	15.0	33	6.8	12	300
	10	SC25-10	18.0	34	6.8	12	300
100	12	SC25-12	18.0	35	6.8	12	300
	14	SC25-14	20.0	38	6.8	12	300
	5	SC35-5	16.0	38	8.2	14	300
150	6	SC35-6	16.0	38	8.2	14	300
	8	SC35-8	16.0	38	8.2	14	300
	10	SC35-10	18.0	39	8.2	14	300
200	12	SC35-12	19.0	40.5	8.2	14	300
	14	SC35-14	20.0	42	8.2	14	300
	6	SC50-6	17.8	45	9.5	16	200
300	8	SC50-8	17.8	45	9.5	16	200
	10	SC50-10	17.8	45	9.5	16	200
	12	SC50-12	20.0	45	9.5	16	200
400	14	SC50-14	22.0	46	9.5	16	200
	16	SC50-16	24.0	47	9.5	16	200
	8	SC70-8	21.0	52	11.2	20	200
500	10	SC70-10	21.0	52	11.2	20	200
	12	SC70-12	21.0	52	11.2	20	200
	14	SC70-14	21.0	52	11.2	20	200
630	16	SC70-16	25.0	53	11.2	20	200

Copper tube terminal

SC



Features:
● SC series terminal is made from T2 copper tube, via the tinning treatment, can avoid oxidation, the size of special copper tube makes the electrical conductivity is the best, and guarantees mechanical strength. After high temperature annealing treatment, the ductility is optimal.

*If you have special needs, please contact Tianze Electric Power Group

Conductor size mm ²	Stud mm	Part No.	Dimension mm				MOQ/Bag
			B	L	φd	L1	
95	8	SC95-8	25.0	58	13.5	23	100
	10	SC95-10	25.0	58	13.5	23	100
	12	SC95-12	25.0	58	13.5	23	100
120	14	SC95-14	25.0	58	13.5	23	100
	16	SC95-16	25.0	58	13.5	23	100
	8	SC120-8	28.0	63	15.0	24	100
150	10	SC120-10	28.0	63	15.0	24	100
	12	SC120-12	28.0	63	15.0	24	100
	14	SC120-14	28.0	63	15.0	24	100
185	16	SC120-16	28.0	63	15.0	24	100
	20	SC120-20	28.0	63	15.0	24	100
	8	SC150-8	30.5	70	16.5	26	100
240	10	SC150-10	30.5	70	16.5	26	100
	12	SC150-12	30.5	70	16.5	26	100
	14	SC150-14	30.5	70	16.5	26	100
300	16	SC150-16	30.5	70	16.5	26	100
	20	SC150-20	30.5	70	16.5	26	100
	10	SC185-10	34.0	75	18.5	32	100
400	12	SC185-12	34.0	75	18.5	32	100
	14	SC185-14	34.0	75	18.5	32	100
	16	SC185-16	34.0	75	18.5	32	100
500	20	SC185-20	34.0	75	18.5	32	100
	10	SC240-10	38.5	90	21.0	32	100
	12	SC240-12	38.5	90	21.0	32	100
630	14	SC240-14	38.5	90	21.0	38	100
	16	SC240-16	38.5	90	21.0	38	100
	20	SC240-20	38.5	90	21.0	38	100
800	10	SC300-10	43.0	98	23.5	42	50
	12	SC300-12	43.0	98	23.5	42	50
	14	SC300-14	43.0	98	23.5	42	50
1000	16	SC300-16	43.0	98	23.5	42	50
	20	SC300-20	43.0	98	23.5	42	50
	10	SC400-10	52.0	110	28.5	44	50
1250	12	SC400-12	52.0	110	28.5	44	50
	14	SC400-14	52.0	110	28.5	44	50
	16	SC400-16	52.0	110	28.5	44	50
1600	20	SC400-20	52.0	110	28.5	44	50
	10	SC500-10	56.0	120	30.0	48	50
	12	SC500-12	56.0	120	30.0	48	50
2000	14	SC500-14	56.0	120	30.0	48	50
	20	SC500-20	56.0	120	30.0	48	50
	10	SC630-10	65.0	140	35.0	56	50
2500	12	SC630-12	65.0	140	35.0	56	50
	14	SC630-14	65.0	140	35.0	56	50
	16	SC630-16	65.0	140	35.0	56	50
3150	20	SC630-20	65.0	140	35.0	56	50